



DESCRIPTION

Ultra Performance Color Specific Caulk is hybrid adhesive and sealant that is color and texture matched to specific applications. Ultra Performance Caulk is a high grade, fast curing, one component non-sag adhesive and sealant that ideal for use indoor and outdoor applications. Conforms to ASTM C920 Type S, Grade NS, Class 50, Use T, M, G, A, O and TT-S-230C, Type II, Class A

ADVANTAGES

- Interior and exterior use
- Dry and wet applications
- Sanded and Non-sanded
- Fast skin time
- Multiple substrate adhesion
- Mold and mildew resistant
- Easy to tool
- Paintable
- Superior UV resistance
- Extremely low VOC
- Superior flexibility and elongation
- Expansion joints in residential and commercial applications including traffic areas
- 100+ in stock colors
- Ability to color match

COVERAGE

10.3 fl. Oz.Tube covers 24 lineal feet at ¼" by ¼" Joint

10.3 fl. Oz.Tube covers 12 lineal feet at ¼" by ½" Joint

USES

- Interior and exterior use
- Large joints
- Wet areas
- Residential and Commercial
- Expansion Joints including traffic areas
- Joints in ceramic tile and stone applications
- Connecting dissimilar substrates.
Example- vinyl to concrete, wood to aluminum, tile to plastic, etc.
- Change of plane joint- floor to wall.

SUBSTRATES

Steel, Aluminum, Glass, Brick, Block, Wood, Plastic, Ceramic tile, Porcelain, Natural stone, Concrete, Fiberglass, Vinyl.

PACKING

10.3 fl. Oz.Tube, 10 tubes per case
32 fl. Oz.Tube, 10Tubes per case

Service Temperature Range	-40°F to 350°F
Sag or Slump ASTM (D2202)	None
Tack Free Time (ASTM C679)	15-30 Minutes
Tooling Time	5-10 Minutes
Durometer Hardness (Shore A) (ASTM C661)	25 Non-sanded and 35 Sanded
Tensile Strength(ASTM D412)	300 psi (2.06 Mpa)
Joint Movement (ASTM C920)	+/-50%
Weatherability (QUV Weatherometer)	Excellent
VOC	N/D, so small cannot be detected
Freeze/Thaw cycles	2 Cycles
Elongation (ASTM D412)	350% Sanded, 500% Non-sanded