

**\*SHAKE WELL. SHAKE EVERY 3 MINUTES WHEN USING**

This material will remove grease, oil and grime from tile and other surfaces. Do not use on porous tiles.

It will help remove epoxy haze when used within 24 hours of application. Optimum temperature to use this product is 65°F to 75°F.

**LIMITATIONS:** This product is not designed to remove dried epoxy on the surface of the tile and it is not to replace careful cleanup for epoxies at the time they're applied.

**\*NOTE:** ALWAYS LABEL CONTAINER WITH PRODUCT NAME AND DILUTION RATIO.

**APPLICATION:** Apply liberally to surface, let set for 3 to 5 minutes. Use a stiff bristle brush for grout joints or a nylon scrub pad for surfaces and vigorously scrub areas. To remove heavily soiled material from the surface CLEAN with cool water using a sponge. Repeat if necessary. If using this product to remove haze left over from grout colorant, DO NOT SCRUB GROUT JOINT DIRECTLY! Make sure you use a towel to buff the tile and to remove any leftover product or haze.

**KEEP OUT OF REACH OF CHILDREN.**

**DO NOT TAKE INTERNALLY, KEEP FROM FREEZING.**

**ONE YEAR SHELF LIFE (FROM DATE OF MANUFACTURE).**

**CAUTION:** Wear rubber gloves and protective eyewear. Avoid contact with eyes or prolonged contact with skin. In case of eye contact, flush eyes with water. Call a physician immediately.

**Ingredients:** Water C.A.S. #77323-18-5, D-Limonene C.A.S. #5989-27-5, Potassium tripolyphosphate C.A.S. #13845-36-8.

***COLORFAST INDUSTRIES, INC.***

COLTON, CA

**\*SHAKE WELL. SHAKE EVERY 3 MINUTES WHEN USING**

This material will remove grease, oil and grime from tile and other surfaces. Do not use on porous tiles.

It will help remove epoxy haze when used within 24 hours of application. Optimum temperature to use this product is 65°F to 75°F.

**LIMITATIONS:** This product is not designed to remove dried epoxy on the surface of the tile and it is not to replace careful cleanup for epoxies at the time they're applied.

**\*NOTE:** ALWAYS LABEL CONTAINER WITH PRODUCT NAME AND DILUTION RATIO.

**MIXING:** For heavy duty use, mix 2 parts cool water to 1 part cleaner. For medium cleaning, mix 5 parts cool water to 1 part cleaner. For light duty cleaning, Mix 10 parts cool water to 1 part cleaner. **NOTE:** ALWAYS LABEL MIXING CONTAINER WITH PRODUCT NAME AND DILUTION RATIO.

**APPLICATION:** Apply liberally to surface, let set for 3 to 5 minutes. Use a stiff bristle brush for grout joints or a nylon scrub pad for surfaces and vigorously scrub areas. To remove heavily soiled material from the surface CLEAN with cool water using a sponge. Repeat if necessary. If using this product to remove haze left over from grout colorant, DO NOT SCRUB GROUT JOINT DIRECTLY! Make sure you use a towel to buff the tile and to remove any leftover product or haze.

**KEEP OUT OF REACH OF CHILDREN.**

**DO NOT TAKE INTERNALLY, KEEP FROM FREEZING.**

**ONE YEAR SHELF LIFE (FROM DATE OF MANUFACTURE).**

**CAUTION:** Wear rubber gloves and protective eyewear. Avoid contact with eyes or prolonged contact with skin. In case of eye contact, flush with water. Call a physician immediately.

**Ingredients:** Water C.A.S. #77323-18-5, D-Limonene C.A.S. #5989-27-5, Potassium Tripolyphosphate C.A.S. #13845-36-8.

***COLORFAST INDUSTRIES, INC.***

COLTON, CA