

INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may administer oxygen. Call a physician.

**NOTICE TO PHYSICIAN**

N/A

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Soak up with absorbant material and remove to closed container. Wash area with mild detergent and water. Dispose of in accordance with local, state and federal EPA regulations.

**WASTE DISPOSAL METHOD**

Dispose of in accordance with Local, State and federal regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep away from children. Do not get in eyes, on skin or clothing. Do not take internally. Keep container closed when not in use. Avoid breathing vapor. Wash thoroughly after handling and before eating or drinking. Use with adequate ventilation. Flammable liquid, do not expose to sources of ignition.

**OTHER PRECAUTIONS**

No eating or drinking should be allowed in the vicinity of this material. Smoking in the area where this material is used should be strictly prohibited. Tools used with this material should be non sparking.

## ===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

Do not breath vapors, spray mist or sanding dust. When spray applied in outdoor or open areas and during sanding or grinding operations, use NIOSH/MSHA approved mechanical filter respirator to remove solid airborne particles of overspray and sanding dist. When used in restricted ventilation areas, wear NIOSH/MSHA approved chemical/mechanical filter designed to remove a combination of particulates and vapor. When used in confined areas, wear NIOSH/MSHA approved air supply respirators or use hoods. Use NIOSH/MSHA approved respirator when flame cutting, welding, brazing and sanding material coated with this product.

**VENTILATION**

Provide general dilution or local exhaust venilation in volume and pattern to keep the air contaminant concentration below current applicable safety and health standards in the mixing, application and curing areas and to remove the sanding dusts and dried coatings and decomposition products during welding and flame cutting on surfaces coated with this product. Vapors may spread long distances. Prevent build-up by removing heavy solvent vapoars from lower levels of the work area. Eliminate all ignition sources.

**PROTECTIVE GLOVES**

Impermeable recommended.

**EYE PROTECTION**

Solvent resistant safety eyewear with splash guards or side shields is recommended. Contact lenses should not be worn.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Eye wash facility and safety shower recommended. Use impermeable aprons and protective clothing whenever possible to prevent skin contact.

**WORK/HYGIENIC PRACTICES**

Wash hands with soap and water after using and before eating or drinking.

## ===== SECTION IX - REGULATORY INFORMATION =====

PROPER SHIPPING NAME :