

M A T E R I A L S A F E T Y D A T A S H E E T

EPOXY GROUT TINT BASE SANDED PART {A}

Page: 1

PRODUCT NAME: EPOXY GROUT TINT BASE SANDED PART {A}
PRODUCT CODE: EPOXY GROUT TINT

HMIS CODES: H F R P
1 0 1 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Color Fast Industries, Inc.
ADDRESS : 350 West H Street
Colton, CA 92324

EMERGENCY PHONE : (888) 600-0476 DATE PRINTED : 05/18/98
INFORMATION PHONE : (909) 514-1458 NAME OF PREPARER : Dexter Tuttle

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
Epoxy Resin	proprietary	<20	20 C
TITANIUM DIOXIDE	13463-67-7		

N/A

ABBREVIATIONS: NE - NOT ESTABLISHED, NA - NOT APPLICABLE, [CL] - CEILING LIMIT, D - NUISANCE PARTICLE TVL 10 MG/M3 TOTAL DUST, [C] - CARCINOGEN, [PC] - POTENTIAL CARCINOGEN, DD - INERT OR NUISANCE DUST PEL 15 MG/M3 TOTAL DUST, [1] - NOT ESTABLISHED OR USE STODDARD SOLVENT AS A GUIDE.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.83
VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than Ether
COATING V.O.C.: 0.00 lb/gl MATERIAL V.O.C.: 0.00 lb/gl
SOLUBILITY IN WATER: PARTIAL
APPEARANCE AND ODOR: WHITE OR COLORED SANDED PASTE SLIGHT EPOXY SMELL

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
Not flammable.

UNUSUAL FIRE AND EXPLOSION HAZARDS
N/A

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable
CONDITIONS TO AVOID
Avoid excessive heat

INCOMPATIBILITY (MATERIALS TO AVOID)
No specific incompatibilities.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS