

MATERIAL SAFETY DATA SHEET

GROUT COLORANT WHITE

Page: 1

PRODUCT NAME: GROUT COLORANT WHITE

HMIS CODES: H F R P

PRODUCT CODE: GCWHITE

1 0 1

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Color Fast Industries, Inc.

ADDRESS : 350 West H Street
Colton, CA 92324

EMERGENCY PHONE : (888) 600-0476

DATE PRINTED : 06/26/96

INFORMATION PHONE : (909) 514-1458

NAME OF PREPARER : Dexter Tuttle

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 4 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE mm Hg @ TEMP, WEIGHT PERCENT. Rows include WATER, MODIFIED BISPHENOL A A-ECH BASED EPOXY RESIN, 2-PROPOXYETHANOL, SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC.

N/A

ABBREVIATIONS: NE - NOT ESTABLISHED, NA - NOT APPLICABLE, [CL] - CEILING LIMIT, D - NUISANCE PARTICLE TVL 10 MG/M3 TOTAL DUST, [C] - CARCINOGEN, [PC] - POTENTIAL CARCINOGEN, DD - INERT OR NUISANCE DUST PEL 15 MG/M3 TOTAL DUST, [I] - NOT ESTABLISHED OR USE STODDARD SOLVENT AS A GUIDE.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.04
VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than Ether
COATING V.O.C.: -0.01 lb/gl MATERIAL V.O.C.: 0.12 lb/gl
SOLUBILITY IN WATER: Dispersible.
APPEARANCE AND ODOR: Tinted viscous liquid with mild odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Not flammable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

N/A

SECTION V - REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID

Avoid excessive heat

INCOMPATIBILITY (MATERIALS TO AVOID)

Can react vigorously with strong oxidizing agents, lewis or mineral acids, and strong mineral or organic bases/espically primary and