

SEAM ADHEASIVE AND FILLER TINT BASE

PRODUCT NAME: SEAM ADHEASIVE AND FILLER TINT BASE

HMS CODES: H F R P

PRODUCT CODE: SAF-TINT BASE

3 1 3 B

SECTION I MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Color Fast Industries, Inc
 ADDRESS : 350 West H Street
 Colton, CA 92324

EMERGENCY PHONE (888) 600-0476 DATE PRINTED : 06/14/99
 INFORMATION PHONE (909) 514-1458 NAME OF PREPARER : Dexter Tuttle

SECTION II HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @	TEMP	PERCENT
Epoxy Curing agent	proprietary	<20	20 C	64
PRODUCT CONTAINS TETRAETHYLENEPENTAMINE CAS#112-57-2 >12% 1.0 PPM PART B				
TITANIUM DIOXIDE	13463-67-7			11

N/A

ABBREVIATIONS: NE - NOT ESTABLISHED, NA - NOT APPLICABLE, [CL] - CEILING LIMIT, D - NUISANCE PARTICLE TVL 10 MG/M3 TOTAL DUST, [C] - CARCINOGEN, [PC] - POTENTIAL CARCINOGEN, DD - INERT OR NUISANCE DUST PEL 15 MG/M3 TOTAL DUST, [1] - NOT ESTABLISHED OR USE STODDARD SOLVENT AS A GUIDE.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.42
 VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than Ether
 COATING V.O.C.: 0.00 lb/gl MATERIAL V.O.C.: 0.00 lb/gl
 SOLUBILITY IN WATER: PARTIAL
 APPEARANCE AND ODOR: WHITE OR COLORED PASTE SLIGHT EPOXY SMELL

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A METHOD USED: N/A
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Not flammable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

N/A

SECTION V REACTIVITY DATA

STABILITY: Stable
 CONDITIONS TO AVOID

Avoid excessive heat

INCOMPATIBILITY (MATERIALS TO AVOID)

No specific incompatibilities.