

Ultra Performance Color Specific Caulk

Safety Data Sheet

SECTION 1: Identification

1.1. Identification

Product name : Ultra Performance Color Specific Caulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Caulk

1.3. Details of the supplier of the safety data sheet

Color Fast Industries, Inc.

912 W Hwy 67

Alvarado, TX 76009

T 817-546-4910

1.4. Emergency telephone number

Emergency number : Chemtrec 1 800 424 9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Eye Irrit. 2 H319

Skin Sens. 1 H317

Muta. 2 H341

Carc. 1B H350

Repr. 2 H361

STOT SE 1 H370

STOT RE 1 H372

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS07

GHS08

Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H361 - Suspected of damaging fertility or the unborn child
H370 - Causes damage to organs
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311 - If exposed: Call a poison center/doctor.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

Ultra Performance Color Specific Caulk

Safety Data Sheet

P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Carbonic acid, calcium salt (1:1)	(CAS-No.) 471-34-1	Trade Secret	Not classified
Titanium dioxide	(CAS-No.) 13463-67-7	Trade Secret	Carc. 2, H351
Chloroform	(CAS-No.) 67-66-3	Trade Secret	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 Repr. 2, H361 STOT SE 3, H336 STOT RE 1, H372
Acrylonitrile	(CAS-No.) 107-13-1	Trade Secret	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 3, H335 Aquatic Chronic 2, H411
2-Pentanone, 4-methyl-	(CAS-No.) 108-10-1	Trade Secret	Flam. Liq. 2, H225 Carc. 2, H351
Phenyl glycidyl ether	(CAS-No.) 122-60-1	Trade Secret	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335
Ethyl acrylate	(CAS-No.) 140-88-5	Trade Secret	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335
Methyl alcohol	(CAS-No.) 67-56-1	Trade Secret	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
Epichlorohydrin	(CAS-No.) 106-89-8	Trade Secret	Flam. Liq. 3, H226 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Immediately call a poison center or doctor/physician.
First-aid measures after skin contact : Wash skin with soap and water for at least 20 minutes. Remove and isolate contaminated clothing and shoes. Call 911 or emergency medical services.

Ultra Performance Color Specific Caulk

Safety Data Sheet

First-aid measures after eye contact : Flush eyes with plenty of water for at least 20 minutes. Call 911 or emergency medical services.

First-aid measures after ingestion : If a large amount is swallowed, call 911 or emergency medical services.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use dry chemical, carbon dioxide, water spray, regular foam.

Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Fire hazard : None known.

Explosion hazard : None known.

5.3. Advice for firefighters

Protection during firefighting : Firefighters should wear full protective gear. Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Isolate area. Keep unnecessary personnel away.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if possible without personal risk.

Methods for cleaning up : Small spills: Absorb with sand or other non-combustible material and place material into appropriate containers for later disposal. Large spills: Dike far ahead of liquid spill for later disposal. Prevent entry into waterways, sewers, basements or confined areas.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Empty containers may contain residual liquid; therefore, empty containers should be handled with care.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.106. Store in a tightly closed container. Store in a cool, dry, place. Protect from direct sunlight, heat, or freezing. Material should be stored in appropriate secondary containers or in a diked area. Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Keep separated from incompatible substances.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)

ACGIH

ACGIH TWA (mg/m³)

10 mg/m³

Ultra Performance Color Specific Caulk

Safety Data Sheet

Titanium dioxide (13463-67-7)		
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Acrylonitrile (107-13-1)		
ACGIH	ACGIH TWA (ppm)	2 ppm
OSHA	OSHA PEL (TWA) (ppm)	2 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	10 ppm
IDLH	US IDLH (ppm)	60 ppm
NIOSH	NIOSH REL (TWA) (ppm)	1 ppm
NIOSH	NIOSH REL (ceiling) (ppm)	10 ppm
Chloroform (67-66-3)		
ACGIH	ACGIH TWA (ppm)	10 ppm
OSHA	OSHA PEL (Ceiling) (mg/m ³)	240 mg/m ³
OSHA	OSHA PEL (Ceiling) (ppm)	50 ppm
IDLH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	9.78 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	2 ppm
Carbonic acid, calcium salt (1:1) (471-34-1)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
2-Pentanone, 4-methyl- (108-10-1)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	205 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	300 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	75 ppm
Phenyl glycidyl ether (122-60-1)		
ACGIH	ACGIH TWA (ppm)	0.1 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	60 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	10 ppm
IDLH	US IDLH (ppm)	100 ppm
NIOSH	NIOSH REL (ceiling) (mg/m ³)	6 mg/m ³
NIOSH	NIOSH REL (ceiling) (ppm)	1 ppm
Ethyl acrylate (140-88-5)		
ACGIH	ACGIH TWA (ppm)	5 ppm
ACGIH	ACGIH STEL (ppm)	15 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	100 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	25 ppm
IDLH	US IDLH (ppm)	300 ppm
Epichlorohydrin (106-89-8)		
ACGIH	ACGIH TWA (ppm)	0.5 ppm

Ultra Performance Color Specific Caulk

Safety Data Sheet

Epichlorohydrin (106-89-8)		
OSHA	OSHA PEL (TWA) (mg/m ³)	19 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	5 ppm
IDLH	US IDLH (ppm)	75 ppm
Methyl alcohol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm

8.2. Exposure controls

Appropriate engineering controls	: Local exhaust and general ventilation must be adequate to meet exposure standards.
Hand protection	: protective gloves.
Eye protection	: Wear splash resistant safety glasses with side-shields. In cases of heavy use or splattering, additional protection, such as a face-shield may be worn.
Skin and body protection	: Wear suitable working clothes.
Respiratory protection	: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Color	: Various
Odor	: None
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 200 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1 – 1.6
Solubility	: Insoluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available

Ultra Performance Color Specific Caulk

Safety Data Sheet

Explosive properties : No data available
 Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

10.5. Incompatible materials

Oxidizing materials, acids, amines, strong caustics, water.

10.6. Hazardous decomposition products

Thermal decomposition products: oxides of carbon, oxides of nitrogen, aldehydes, various polymer compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
Acrylonitrile (107-13-1)	
LD50 oral rat	193 mg/kg
LD50 dermal rabbit	63 mg/kg
LC50 inhalation rat (mg/l)	0.47 mg/l/4h
ATE US (oral)	193 mg/kg body weight
ATE US (dermal)	63 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	0.47 mg/l/4h
ATE US (dust, mist)	0.47 mg/l/4h
Chloroform (67-66-3)	
LD50 oral rat	450 mg/kg
LD50 dermal rabbit	> 20 g/kg
LC50 inhalation rat (mg/l)	47702 mg/m ³ (Exposure time: 4 h)
ATE US (oral)	450 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
Carbonic acid, calcium salt (1:1) (471-34-1)	
LD50 oral rat	6450 mg/kg
ATE US (oral)	6450 mg/kg
2-Pentanone, 4-methyl- (108-10-1)	
LD50 oral rat	2080 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	8.2 mg/l/4h
ATE US (oral)	2080 mg/kg body weight
ATE US (dust, mist)	8.2 mg/l/4h
Phenyl glycidyl ether (122-60-1)	
LD50 oral rat	2600 mg/kg

Ultra Performance Color Specific Caulk

Safety Data Sheet

Phenyl glycidyl ether (122-60-1)	
LD50 dermal rabbit	1500 mg/kg
LC50 inhalation rat (ppm)	> 100 ppm (Exposure time: 8 h)
ATE US (oral)	2600 mg/kg body weight
ATE US (dermal)	1500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Ethyl acrylate (140-88-5)	
LD50 oral rat	550 mg/kg
LD50 dermal rabbit	1790 mg/kg
LC50 inhalation rat (ppm)	1410 ppm/4h
ATE US (oral)	550 mg/kg body weight
ATE US (dermal)	1790 mg/kg body weight
ATE US (gases)	1410 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Epichlorohydrin (106-89-8)	
LD50 oral rat	90 mg/kg
LD50 dermal rabbit	515 mg/kg
LC50 inhalation rat (mg/l)	0.95 mg/l/4h
ATE US (oral)	90 mg/kg
ATE US (dermal)	515 mg/kg

Methyl alcohol (67-56-1)	
LD50 oral rat	6200 mg/kg
LD50 dermal rabbit	15840 mg/kg
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: May cause cancer.

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Acrylonitrile (107-13-1)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes
In OSHA Specifically Regulated Carcinogen list	Yes

Chloroform (67-66-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

2-Pentanone, 4-methyl- (108-10-1)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

Ultra Performance Color Specific Caulk

Safety Data Sheet

2-Pentanone, 4-methyl- (108-10-1)	
In OSHA Hazard Communication Carcinogen list	Yes
Phenyl glycidyl ether (122-60-1)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
Ethyl acrylate (140-88-5)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 4 - Substances delisted from report on Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
Epichlorohydrin (106-89-8)	
IARC group	2A - Probably carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Causes damage to organs.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

Acrylonitrile (107-13-1)	
LC50 fish 1	6.7 – 15 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	7.38 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	8.0 – 12.0 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Chloroform (67-66-3)	
LC50 fish 1	71 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	29 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
2-Pentanone, 4-methyl- (108-10-1)	
LC50 fish 1	496 – 514 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	170 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Ethyl acrylate (140-88-5)	
LC50 fish 1	4.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	7.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.31 – 2.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Epichlorohydrin (106-89-8)	
LC50 fish 1	35 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	24 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	35 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [semi-static])
Methyl alcohol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

Ultra Performance Color Specific Caulk

Safety Data Sheet

12.3. Bioaccumulative potential

Acrylonitrile (107-13-1)	
BCF fish 1	48
Partition coefficient n-octanol/water (Log Pow)	-0.92
Chloroform (67-66-3)	
BCF fish 1	1.4 – 13
Partition coefficient n-octanol/water (Log Pow)	2 (at 25 °C)
Carbonic acid, calcium salt (1:1) (471-34-1)	
BCF fish 1	(no bioaccumulation)
2-Pentanone, 4-methyl- (108-10-1)	
Partition coefficient n-octanol/water (Log Pow)	1.19
Ethyl acrylate (140-88-5)	
Partition coefficient n-octanol/water (Log Pow)	1.18 (at 25 °C)
Epichlorohydrin (106-89-8)	
Partition coefficient n-octanol/water (Log Pow)	0.3 (at 20 °C)
Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Partition coefficient n-octanol/water (Log Pow)	-0.77

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Acrylonitrile (107-13-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb
SARA Section 313 - Emission Reporting	0.1 %

Ultra Performance Color Specific Caulk

Safety Data Sheet

Chloroform (67-66-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb
SARA Section 313 - Emission Reporting	0.1 %
Carbonic acid, calcium salt (1:1) (471-34-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-Pentanone, 4-methyl- (108-10-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %
Phenyl glycidyl ether (122-60-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.
Ethyl acrylate (140-88-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
Epichlorohydrin (106-89-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
Methyl alcohol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %

15.2. US State regulations

Titanium dioxide (13463-67-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	
Acrylonitrile (107-13-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	0.7 µg/day
Chloroform (67-66-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	No	20 µg/day

Ultra Performance Color Specific Caulk

Safety Data Sheet

2-Pentanone, 4-methyl- (108-10-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	No	

Phenyl glycidyl ether (122-60-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	5 µg/day

Ethyl acrylate (140-88-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Epichlorohydrin (106-89-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	Yes	9 µg/day

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Acrylonitrile (107-13-1)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Chloroform (67-66-3)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

2-Pentanone, 4-methyl- (108-10-1)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Phenyl glycidyl ether (122-60-1)

U.S. - Massachusetts - Right To Know List
 U.S. - Minnesota - Hazardous Substance List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Ultra Performance Color Specific Caulk

Safety Data Sheet

Ethyl acrylate (140-88-5)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Epichlorohydrin (106-89-8)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Methyl alcohol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Muta. 2	Germ cell mutagenicity Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Ultra Performance Color Specific Caulk

Safety Data Sheet

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.