

will grout and clean the same as any normal cement grout product, but a 3/16" joint should be left full to allow for shrinkage. A second application may be necessary. See complete installation instructions for additional information.

COVERAGE: Approximately 2 to 4 sq. ft. per 10.3 fl. oz. 25 to 50 sq. ft. per gal.

NOTICE TO PURCHASER: Manufacturers and sellers liability for damages herein shall not exceed the purchase price of the goods used. Manufacturer and seller warrant only that the goods will be free from defects in material. The foregoing warrant is in lieu of all other warranties, express or implied, including those of merchantability of fitness for any purpose not expressly set forth herein. No liability is assumed by manufacturer or seller except as expressly stated herein. In no event shall manufacturer or seller be responsible for incidental or consequential damages arising out of or in connection with the use of this product by user, buyer's user, or any other person.

CAUTION

**KEEP OUT OF REACH OF CHILDREN
KEEP FROM FREEZING**

COLOR FAST INDUSTRIES, INC.
BANNING, CA 92220
WWW.COLORFASTIND.COM

COLORFAST
INDUSTRIES INC.

SYSTEM

1

**ADHESIVE
& GROUT**

**THE ONLY ONE YOU NEED
INSTALLATION
INSTRUCTIONS**

- ✓ Dual-purpose Tile & Grout
- ✓ Pre-Mixed—Ready to Use
- ✓ Stain & Mildew Resistant
- ✓ Stays Flexible—
Resists Cracking
- ✓ Easy Water Cleanup

Preparation and application instructions are based on information we believe reliable. However, you should thoroughly test any application and independently conclude satisfactory performance. Testing for color match before use is required. Installation is color acceptance. If different lot numbers are being used, mix all containers together to provide uniform color and to ensure color consistency. Purchase 10% more than you will need and be sure to get the same lot number.

PREPARATION: All surfaces must be clean, dry, and free of dust, dirt, oil, sealers, loose paint or other foreign material. Damp mop or sponge substrate to remove all dust, dirt, etc. Store adhesive at 65°F for 24 hours before installation, and maintain temperature throughout curing cycle. Provide adequate ventilation. Extremely porous surfaces, such as unpainted plaster, should be primed with a thin film of System 1 Adhesive & Grout. Let cure to seal substrate. **DO NOT SET SOAP DISHES OR TOWEL BARS WITH ADHESIVE & GROUT.** Use Color Fast Silicone Sealant instead. Make certain walls, counters and especially floors are

solid, without spring or give. See installation instructions for substrate preparation.

NOTE: Porous tile may need grout release or sealing before installation.

TROWEL RECOMMENDATIONS:

GLAZED WALL TILE

(4 1/4" or 6" x 6"): 3/16" x 3/16" sawtooth;

FLOOR TILE

(8" x 8" or 12" x 12"): 1/4" x 1/4" notched.

Larger tiles may require larger trowel notch sizes. Special floor preparation must be made for tiles larger than 12" x 12". Floor must be perfectly flat. The use of floor patching and leveling compounds to prepare the floor may be necessary. Follow floor preparation manufacturer's instructions

APPLICATION (ADHESIVE): Always wear rubber gloves. Spread System 1 Adhesive & Grout with appropriate trowel, leaving no bare spots. Spread only enough to set within required open time of 15 to 30 minutes. Press and slide, or twist tile into Adhesive & Grout. Adhesive should push through grout joints. Wipe excess up with a damp sponge. **HELPFUL HINT:** By allowing adhesive to push into grout joints you are pre-grouting tile. Tile must have minimum 95% coverage for

proper bond. Check routinely. It may be necessary to back butter some tiles.

CURING: Let cure 24 hours before grouting. Curing time may vary according to temperature, humidity and substrate.

Avoid walking on floors for 48 hours. If floors must be used, cover floors with boards to dissipate weight.

DO NOT USE ON BUTTON BACK TILE.

APPLICATION (GROUT): RECOMMENDED MAXIMUM SPACE BETWEEN TILES FOR GROUTING FLOORS—3/16", FOR WALLS—1/8". Damp sponge tile before grouting. Always wear rubber gloves. Fill and compact grout joint using COYOTE RUBBER FLOAT. Remove excess grout from the tile surface with float. When haze appears, clean with damp cheese cloth or sponge, then polish with dry cheese cloth.

DO NOT LET FILM DRY ON TILE.

CURING: Let cure for 48 to 72 hours for walls and counters and 1 week for floors, depending on humidity and temperature.

HELPFUL HINT: This product is water soluble when uncured. Some shrinkage is expected. The smaller the grout joint the less the shrinkage. Example: a 1/8" joint